

# **Delta Fishing Light**

# A Revolutionary Light for Fishing

- · 70% Energy Saving
- · Enhances Catch Yields via Special Spectrum
- · Withstands Harsh Environments
- · Safer and Healthier







## LEDs are the future trend for fishing

#### Specific optical design for fishing

LED luminaire vs. Traditional HID lamp, LED direct light is more efficient





Two-Color switching that applies to fish variety





#### 1.5 year payback period

LED fishing light cost savings up to 70%



LED fishing light cost savings up to 70%



### **Health and Safety**

No high temperature burns, prevents skin and eye damage





# **Advantages of LED fishing lights**

#### **Exclusive LED spectrum enhances catch yields**

Underwater brightness surpasses traditional light bulbs

Enhances catch yields





#### **Certified protection in harsh conditions**

Meets the regulatory requirements for vibration testing of ship equipment



Protects against mechanical impacts IK10 Anti-glass explosion



Protects against dust and water - IP66



#### **Certified protection in harsh conditions**

World No.1 power solution provider



High performance High quality

Switches right on



Patented dissipation fan Easy installation, Ultra lightweight



Innovative air cooling system, protects against heavy sea waves and against salt erosion





#### **Installation cases**

Kaohsiung Man Shuen Fa - Squid lights







Kaohsiung Zi Da Ye - Squid lights



Kaohsiung Xing Hua Sheng - Saury lights



Philippines - Sardin, Squid lights



Kaohsiung Man Shuen Fa - Squid lights



Shantung - Squid lights



Kaohsiung Win Far Tsair - Squid lights



Kaohsiung Zi Da Ye - Squid lights



Kaohsiung Jia Long - Saury lights



Thailand - Squid lights



Kaohsiung Zi Da Wang - Squid lights



Shantung - Squid lights



Yilan Gengfang - Squid lights



Penghu - Saury lights



Kaohsiung Jia Long - Saury lights



Bali - Squid lights



## **Specifications**



Fishing Light For Saury

| Model Name                             | FLSFA12R5D1FHT                  | FLSFA12RGD1FHT |  |  |
|--|---------------------------------|----------------|--|--|
| Input Voltage                          | 220 - 440 Vac                   |                |  |  |
| Output Lumen (Im)                      | 51,000 / 115,000 51,000 / 81,00 |                |  |  |
| Wattage (W)                            | 1,200                           |                |  |  |
| LED Color<br>(Two-Color Switching)     | Red / 5000K                     | Red / Green    |  |  |
| Beam Angle (º)                         | 120                             |                |  |  |
| Operating Temp (°C)                    | -20 ~ +45 -20 ~ +46             |                |  |  |
| IP                                     | IP66                            |                |  |  |
| Dimensions (mm)<br>(Without U-Bracket) | 431(L) x 415(W) x 144(H)        |                |  |  |
| Weight (Kg)<br>(Without U-Bracket)     | 13.5                            |                |  |  |

| 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - |  |
|---|--|
|   |  |
|   |  |

Fishing Light For Squid

| Model Name                             | FLSFA124CD1FHT           |  |
|--|--------------------------|--|
| Input Voltage                          | 220 - 440 Vac            |  |
| Output Lumen (Im)                      | 125,000                  |  |
| Efficiency (Im/W)                      | 104                      |  |
| Wattage (w)                            | 1,200                    |  |
| LED Color                              | 4000K + Booster Spectrum |  |
| CRI                                    | >70                      |  |
| Beam Angle (º)                         | 120                      |  |
| Operating Temp (°C)                    | -20 ~ +45                |  |
| IP                                     | IP66                     |  |
| Dimensions (mm)<br>(Without U-Bracket) | 431(L) x 415(W) x 144(H) |  |
| Weight (Kg) (Without U-Bracket)        | 13.5                     |  |



All In One (Saury, squid, Migratory fishes)

| Model Name                             | FLSFA12RCD1FHT                   | FLSFA12RDD1FHT                   |  |
|--|----------------------------------|----------------------------------|--|
| Input Voltage                          | 220 - 440 Vac                    |                                  |  |
| Output Lumen (Im)                      | 51,000 / 115,000<br>1,200        |                                  |  |
| Wattage (w)                            |                                  |                                  |  |
| LED Color<br>(TWO-Color Switching)     | Red / 4000K+<br>Booster Spectrum | Red / 5000K+<br>Booster Spectrum |  |
| Beam Angle (°)                         | 120                              |                                  |  |
| Operating Temp (°c)                    | -20 ~ +45                        |                                  |  |
| IP                                     | IP66                             |                                  |  |
| Dimensions (mm)<br>(Without U-Bracket) | 431(L) x 415(W) x 144(H)         |                                  |  |
| Weight (Kg)<br>(Without U-Bracket)     | 13.5                             |                                  |  |

# **Global Operations**

Delta Group has 158 sales offices, 48 plant sites, and 72 R&D centers, with over 9,000 R&D engineers throughout the world.

| Main | Sales | Offices |
|------|-------|---------|
| Main | Plant | Sites   |

| Main | R&D | Cen | ters |
|------|-----|-----|------|

|                      | Asia-Pacific | Americas | EMEA | Total |
|----------------------|--------------|----------|------|-------|
| Global Sales Offices | 100          | 25       | 33   | 158   |
| Global Plant Sites   | 40           | 4        | 4    | 48    |
| Global R&D Centers   | 48           | 9        | 15   | 72    |





#### Delta Electronics, Inc.

No.16 Tungyuan Road, ChungLi Industrial Zone, Taoyuan City 32063, Taiwan TEL: +886-3-452 6107 FAX: +31-20-655-0999 LS.Sales@deltaww.com

